



ACUNTO GAS & ELECTRICAL REQUIREMENTS DOCUMENT

SERIES: ACUNTO NAPOLI OVENS



Acunto Angolare



Acunto Circolare



Acunto Vesuvio

GAS REQUIREMENTS

(Only for gas-fired configurations - does not apply to wood-fired ovens.)

This equipment may be used with LP gas or natural gas.

CONNECTION SIZE:	3/4" Male threaded			
GAS PRESSURE:	LP GAS		NATURAL GAS	
	11-14 in H ₂ O		5.5 - 14 in H ₂ O	
ORIFICE SIZE:	●	○	●	○
	#30		#5	
HOURLY BTU INPUT RATING:	28,000 Btu/Hr	140,000 Btu/Hr	28,000 Btu/Hr	140,000 Btu/Hr

● MINIMUM BTU

○ MAXIMUM BTU

(Burner uses an automatic modulation control system that adjusts BTU according to need.)

- Gas-fired ovens must be special-ordered from Italy and require additional lead time.
- Acunto Ovens are fully cured at the Fiero Group facility before delivery.

ELECTRICAL REQUIREMENTS

VOLTAGE: 120V	CURRENT: 1.5A	FREQUENCY: 60Hz	PHASE: 1-Phase
---------------	---------------	-----------------	----------------

Supplied with a NEMA 5-15 type grounded plug

FIERO GROUP
 601 N Main St, Brewster, NY 10509
 Email: info@fierogroup.com
www.fierogroup.com

844-OVEN-INC (844-683-6462)
 Toll-free in USA
 (Hablamos Español,
 Falamos Português)

Listed to: UL 2162, NSF-4
 Commercial Wood-Fired
 Baking Ovens – Refractory Type;
 File#: MH48941

